



ECO-BOND Adhesives, LLC
1343 E. Wisconsin Ave. #110
Pewaukee, WI 53072
800-326-8102
www.ecobondit.com

Multi-Purpose

Non-Toxic Caulk, Construction Adhesive, Sealant, and Silicone Replacement

PRODUCT SPECIFICATIONS:

- Zero VOC's off gassed during curing process
- 100% NON-Toxic, no solvents
- Waterproof
- Fast Tacking
- Non-Yellowing
- Certified Hypoallergenic
- Bonds & Seals Fully Submerged
- Exceeds all CA Standards
- Chemically impervious to all mold and mildew
- No toxic odor
- Paintable within in 2 hours
- No Prop 65 listed materials
- UV resistant
- Earns LEED and NAHB Green Building Points
- Non-Shrinking
- Safe to use indoors
- Non-Flammable
- Non-petroleum based
- Easy to tool

TECHNICAL SPECIFICATIONS:

- Shear strength: 170 psi
- Tensile strength: 166 psi
- Elongation: 250%
- Tack Free Time: 65 minutes
- Cure Rate: 1/4" Bead per 24 Hrs
- Movement Capability: 25%
- UV Rating: Excellent
- Sag: None
- Staining: None

BONDS & SEALS TO:

Aluminum	Plaster
Block and Brick	Plastics
Cement Board	Plywood
Concrete	Rubber
Drywall	Siding
Fiberglass	Steel
Foam	Stone
Glass	Tile
Laminate	Treated Wood
Metal	Two Non-porous Surfaces
Mirrors	Vinyl
Painted Surfaces	Windows
Paneling	Wood

PERFORMANCE STANDARDS:

- OTC Rule for Adhesives
- Meets requirements of CA regulations: CARB, SCAQMD, BAQMD
- CA Prop 65
- USDA requirements for non-food contact

STOCK SIZES:

- 10.1 Ounce Tube

SPECIAL ORDER:

- 2 ounce, 29 ounce, 2 Gallon, 5 Gallon & 55 Gallon
- Color matching available

1-800-ECO-8102

www.ecobondit.com